

You need fresh air, so does your home.



Greentek Peace of Mind

All Greentek products are backed by the best limited warranty in the industry, for your peace of mind.

You benefit from a lifetime warranty on the core, a 10-year warranty on our ventilation motors and a 5-year warranty on all other components. So you can breathe easy.





Imperial.

Heat Recovery Ventilator ENERGY STAR® Rated PH Series (PH 7.15 ES and PH 10.22 ES)





Features & Benefits



DuoTrol balancing system

Silent and economical... By reducing motor speed to balance the unit, you avoid the noise that would be

produced by balancing dampers. In addition, with this technology the unit will consume less energy.



SPM attachment system

The entire line of Greentek HRV/ERV products is designed for installation by a single person. "Single Person Mounting" will enable you

to save time and effort by offering you a variable attachment system.



ISF 6" (diam.) collar system (Patent Pending)

Quick and simple to install thanks to our revolutionary "Insert Slide and Fix"

collar system. The "ISF" 6" (diam.) collar system enables you to manipulate duct within your reach and then insert by sliding it in place, for a better and quicker installation.



Rang e of controls For optimal performance of your HRV/ERV system.

The entire range of GreenThinker controls is offered with features making

your ventilation system simple, easy to operate and backed by a 5-year limited warranty. Choose from: RD-1, RD-2, RD-3P, RD-4P (shown above) and T-3 (Push-Button Timer)




High-Performance motors

All Imperial products are designed with highperformance and reliable motors for your comfort and peace of mind. Factory

sealed and dynamically balanced, our motors are maintenance-free for years to come.

Ventilation Performance PH 7.15 ES								
External Static		Net Supply Air Flow			Gross Air Flow		Gross Air Flow Exhaust	
Pressure					Supply			
_Pa	in. wg	L/s	CFM	L/s	CFM	L/s	CFM	
25	0.1	71	150	72	153	80	170	
50	0.2	64	136	65	138	73	155	
75	0.3	58	123	58	123	66	140	
100	0.4	52	110	52	110	59	125	
125	0.5	47	100	47	100	52	110	
150	0.6	40	85	41	87	47	100	
175	0.7	33	70	33	70	40	85	
This product earned the ENERGY STAR® by meeting strict energy efficiency updeliness set by Natural Resources Canada and the US EPA. It meets NERGY STAR® requirements only when used in Canada.								



Ven [.]	tilation	Perfo	rman	ce PH	10.22	2 ES		
Extern	al Static	Net S	Supply	Gross A	ir Flow	Gross A	ir Flow	
Pres	ssure	Air	Flow	Sup	ply	Exha	ust	
Pa	in. wg	L/s	CFM	L/s	CFM	L/s	CFM	
25	0.1	111	235	112	237	120	254	
50	0.2	102	216	103	218	111	235	
75	0.3	93	197	94	199	102	216	
100	0.4	85	180	86	182	92	195	
125	0.5	78	165	79	167	83	176	
150	0.6	70	148	71	150	75	159	
175	0.7	62	131	63	133	66	140	
HVI CERTIFIED	This product earned the ENERGY STARP by meeting strict energy efficiency guidelines set by Natural Resources Canada and the US EPA. It meets ENERGY STARP requirements only when used in Canada.							

78

51

64

60

Supply - D-Exhaust

250

01

150

0.1

02

0.3

0.4

0.5

0.6

0.7

External Static Pressure in wg (Pa = n x 248.36)

Ξr	nergy	/ Per	form	nanc	ce PH	7.15 ES
		pply erature		et Flow	Power Consumed	Sensible Recovery
	°C	°F	L/s	CFM	Watts	Efficiency
5	0	32	30	64	52	70
ĺ	0	32	40	85	64	65

50 106

33 70

0 32

-13

En	Energy Performance PH 10.22 ES					
	Supply Temperature			et Flow	Power Consumed	Sensible Recovery
	°C	°F	L/s	CFM	Watts	Efficiency
5	0	32	31	66	58	75
HEATING	0	32	43	91	70	73
ĕI	0	32	60	127	88	69
Ŧ	-25	-13	31	66	55	60

SPECIFICATIONS	PH 7.15 ES	PH 10.22 ES
Size	23¾" x 21½" x 11¾"	23%" x 21½" x 16½"
Weight	50 lbs (22.68 Kg)	65 lbs (29.48 Kg)
CFM	30 to 150	50 to 220
Type of heat exchanger	cross-flow (Polypropylene)	cross-flow (Polypropylene)
Exchange surface	104 ft ²	150 ft ²
Voltage	120 VAC @ 60 Hz	120 VAC @ 60 Hz
Amperage	1.0 A	1.5 A
Defrost type	Evacuation	Evacuation
Certification	HVI, _c CSA _{us}	HVI, cCSA _{us}
Rated	ENERGY STAR®	ENERGY STAR®
	211/2" 6"	21½" 6"



Imperial Air Technologies 480 Ferdinand Blvd., Dieppe, NB Canada E1A 6V9 Toll free: 1 888 724-5211

Toll free: 1 888 724-5211 Fax: 1 (506) 388-4633 Visit us at: www.greentek.ca

You can find Greentek Indoor Air Quality products at the following distributor:









Imperial Air Technologies Inc. reserves the right to modify a product, without prior notice, whether in design, colour or specifications, in order to offer at all times a quality product that is highly competitive. Please consult your national and local building codes to find out whether the installation of electrical products requires the services of a certified technician or electrician. GreentekTM is a registered Trademark used under license by Imperial Sheet Metal Ltd. All rights reserved.